

SAFETY DATA SHEET

Date of issue : September 2021

SIMACOVER EP UNICOAT 2401-00 BASE
SECTION 1 Identification of the substance

Trade Name	SIMACOVER EP UNICOAT BASE
Product Code	2401-00
Product Type	Solvent based
Manufacturer's data	PT. SIGMA UTAMA Jl. Landbouw No.1 Citeureup – Bogor, INDONESIA + 62-21-87 3042 (Fax)
Emergency Telephone No.	+ 62-21-87 6310 (Office Hours)

SECTION 2 Hazard identification

OSHA/HCS Status	Considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)
Classification of the substance or mixture	FLAMMABLE LIQUIDS – Category 3 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) – Category 3 AQUATIC TOXICITY (CHRONIC) – Category 2

Label elements
Hazard pictograms


Signal Word	Warning
Hazard Statements	H226- Flammable liquid and vapor H318- Causes serious eye damage H315- Causes skin irritation H317- May cause an allergic skin reaction H410- Very toxic to aquatic life with long lasting effects

Precautionary statements

Prevention	Avoid breathing vapors, spray or mists. Wear protective gloves/protective clothing/eye protection/face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep out of reach of children. Keep container tightly closed. Use personal protective equipment as required.
Response	IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs : get medical attention
Storage	Store in a cool, well-ventilated area Store in a cool, well-ventilated area
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulation
Hazardous ingredients	Xylene, bisphenol A-epichlorohydrin
Other Hazards	None Known

SECTION 3 Composition

Ingredient	CAS No	Conc. range (%)	GHS Classification
Xylene	1330-20-7	5 - 15	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315

SAFETY DATA SHEET

Date of issue : September 2021

SIMACOVER EP UNICOAT 2401-00 BASE

			Eye Irrit. 2;H319 STOT SE 3;H335 Asp. Tox. 1;H304
Bisphenol A -epichlorohydrin	25068-38-6	20 - 35	Skin Irrit H317 Eye Irrit H318 Asp. Tox. H335 Fertility Dam H360
Talc	14807-96-6	25-30	-----
Organophillic clay	-----	<3	Skin Irrit H317 Eye Irrit H318 Asp. Tox. H335 Fertility Dam H360
Silica Flour	14808-6-7	18-20	-----

Concentrations shown as range to protect confidentiality or due to batch variation.

There are no additional ingredients presents which, within the currenet knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and environment and hence require reporting in this section

SECTION 4 First Aid Measure

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If breathing is irregular, drowsiness, loss of consciousness or cramps : call 112 and give immediate treatment (first aid)

Eye contact	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek immediate medical attention.
Inhalation	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and get medical attention immediately
Skin contact	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners
Ingestion	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so that vomit will not re-enter the mouth and throat
Protection of first-aider	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

SECTION 5 Fire Fighting Measure

Extinguishing media	Recommended : Alcohol resistant foam, CO2 ,powder, water spray (foam) Not to be used : water jet
Hazards from the substance or mixture	Flammable liquid and vapor. In a fire or heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	Decomposition products may include the following materials : carbon oxides metal oxide/oxides.

SAFETY DATA SHEET

Date of issue : September 2021

SIMACOVER EP UNICOAT 2401-00 BASE
Special equipment for fire fighter

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6 Accidental release measurement
Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations. Avoid all direct contact with the spilled material. Exclude sources of ignition and be aware of explosion hazard. Ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities

Methods for cleaning up

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g.sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilled product.

SECTION 7 Handling and storage
Handling

Vapor are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should be used only in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. No sparking tools should be used. Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see section 8. Always keep in containers made from the same material as the original one.

Storage

Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from : Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

SECTION 8 Exposure control/personal protection

Ingredient	Exposure limit
Talc	OSHA PEL TWA : 2 mg/m ³
Organophillic clay	OSHA PEL TWA : 10 mg/m ³
Xylene	OSHA 2013 TWA : ppm (435 mg/m ³)

Personal Protection


SAFETY DATA SHEET

Date of issue : September 2021

SIMACOVER EP UNICOAT 2401-00 BASE

Use a NIOSH APPROVED RESPIRATOR
 Use GOGGLES OR FACE SHIELD
 RUBBER GLOVES AS NEEDED
 USE APRON OR OTHER CLOTHING TO AVOID SKIN CONTACT

Personal protective equipment should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Use a properly fitted, air-purifying or air fed respirator complying with an approved standard. Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.

Engineering controls

Keep gas, vapor, or dust concentration below any lower explosive limit. Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location

Hygiene measures

Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filter or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels

SECTION 9 Physical and chemical properties

Physical	Liquid- White, and colour
Odor	Solvent-like
pH	-
Flash point	Closed up ; 50°C
Vapor density	Heavier than air
Specific density	1.50 ± 0.15 kg /litre
Viscosity	25-30 Poise/Str
Solubilities	Insoluble in water

SECTION 10 Stability and reactivity

Reactivity and chemical stability	<p>Conditions to avoid : Avoid temperatures above 60°C (140 F), direct sunlight and contact with sources of heat.</p> <p>Hazardous reactions : Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.</p>
Hazardous decomposition products	<p>Under normal conditions of storage and use, hazardous decomposition products should not be produced</p>
Conditions to avoid	<p>Avoid all possible sources of ignition (spark or flame). Do not pressurized, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition</p>

SECTION 11 Toxicological information

Ingredient	Oral LD 50, mg/kg	Skin LD 50, mg/kg	Inhalation vapor LD 50, mg/l/4 hours
Bisphenol A –epichlorohydrin	4000 mg/kg, rat	20000 rabbit	No data
Xylene	4300 mg/kg, rat	>2000 mg/kg, rabbit	6350 ppm, rat
Silia flour	No data	No data	No data

SAFETY DATA SHEET

Date of issue : September 2021

SIMACOVER EP UNICOAT 2401-00 BASE
SECTION 12 Ecological information

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	96 hr EC50 algae, mg/l
Organophilic clay	>30000 mg/L Acartia Tonsa	>10000 skeletonema costatum	Not Available
Xylene	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales
Bisphenol A – epichlorohydrin	9.4, Marinewater fish	21 days: 3.16, Daphnia magna	96 hours: 1.1 Marinewater algae

Environmental precaution : harmful to aquatic organism, may cause long term adverse effect in the aquatic environment.

SECTION 13 Disposal consideration

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations.

Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Spillage, remains, discarded clothes and similar should be discarded in a fireproof container.

The information presented below only applies to the material as supplied. The identification based on characteristic or listing may not apply if the material has been used or otherwise contaminated.

SECTION 14 Transport information

Transport within user's premises	Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage
----------------------------------	---

	UN no.	Proper shipping name	Transport hazard class(es)	PG*	Env*	Additional information
ADR/RID Class	UN 1263	Paint	3 -	III	Yes	
IMDG Class	UN1263	Paint	3 -	III	Yes	
IATA Class	UN1263	Paint	3 -	III	Yes	

PG* : Packing group

Env* : Environmental hazards

SECTION 15 Regulatory information

Safety, health and environmental regulation/legislation specific for the substance or mixture

SECTION 16 Other information

Abbreviation and acronyms

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

SAFETY DATA SHEET

Date of issue : September 2021

SIMACOVER EP UNICOAT 2401-00 BASE

Disclaimer

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. HOWEVER, NEITHER PT. SIGMA UTAMA NOR ANY SUBSIDIARIES ASSUMES ANY LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIALS MAY PRESENT UNKNOWN HAZARDS AND SHOULD BE USED IN CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CAN NOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS WHICH EXIST.

SAFETY DATA SHEET

Date of issue : September 2021

SIMACOVER EP UNICOAT 2401-00 HARDENER
SECTION 1 Identification of the substance

Trade Name	SIMACOVER EP UNICOAT HARDENER
Product Code	2401-00
Product Type	Solvent based
Manufacturer's data	PT. SIGMA UTAMA Jl. Landbouw No.1 Citeureup – Bogor, INDONESIA + 62-21-87 3042 (Fax)
Emergency Telephone No.	+ 62-21-87 6310 (Office Hours)

SECTION 2 Hazard identification

OSHA/HCS Status	Considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)
Classification of the substance or mixture	FLAMMABLE LIQUIDS – Category 3 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) – Category 3 AQUATIC TOXICITY (CHRONIC) – Category 2

Label elements

Hazard pictograms



Signal Word	Warning
Hazard Statements	H226- Flammable liquid and vapor H318- Causes serious eye damage H315- Causes skin irritation H317- May cause an allergic skin reaction H410- Very toxic to aquatic life with long lasting effects

Precautionary statements

Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapor. Wash hands thoroughly after handling.
Response	Collect spillage. Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get a medical if you feel unwell. IF SWALLOWED: Immediately call a medical center. Do not induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	Store locked up Store in a cool, well-ventilated area Store in a cool, well-ventilated area

SAFETY DATA SHEET

Date of issue : September 2021

SIMACOVER EP UNICOAT 2401-00 HARDENER

Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulation
Supplemental label elements	Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and receiving equipment. These alone may be insufficient to remove static electricity. Avoid contact with skin and clothing. Wash thoroughly after handling.
Hazards not otherwise classified	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor may cause flash fire or explosion. Prolonged or repeated contact may dry skin and cause irritation. Repeated or prolonged overexposure to certain chemicals in this product may exacerbate the hearing loss effects associated with noise exposure.
Hazardous ingredients Other Hazards	Xylene, ethylenediamine, None Known

SECTION 3 Composition

Ingredient	CAS No	Conc. range (%)	GHS Classification
Xylene	1330-20-7	12-17	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315 Eye Irrit. 2;H319 STOT SE 3;H335 Asp. Tox. 1;H304
Ethylenediamine	107-15-3	2-5	H334 Skin Irrit H317 Flam. Liq. 3;H226 Acute Tox. 4;H312 Skin Corr. 1B, H314 Acute Tox. 4, H302
Methyl isobutyl ketone	108-10-1	5-10	Flam. Liq. 2, H225 Eye Irrit. 2;H319 Acute Tox. 4;H332 STOT SE 3;H335
Methyl ethyl ketone	78-93-3	5-10	Eye Irrit. 2;H319 Flam. Liq. 2, H225 H336
Isobutanol	78-83-1	5-10	Flam. Liq. 3;H226 Skin Irrit. 2;H315 EyeDam.1,H318, STOTSE3, H335

Concentrations shown as range to protect confidentiality or due to batch variation.

There are no additional ingredients presents which, within the currenet knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and environment and hence require reporting in this section

SECTION 4 First Aid Measure

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If breathing is irregular, drowsiness, loss of consciousness or cramps : call 112 and give immediate treatment (first aid)

Eye contact Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Continue to rinse for at least 10 minutes. Seek immediate medical attention.

Inhalation Remove victim to fresh air, and keep person at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial

SAFETY DATA SHEET

Date of issue : September 2021

SIMACOVER EP UNICOAT 2401-00 HARDENER

respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and get medical attention immediately

Skin contact Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners

Ingestion Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aider No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

SECTION 5 Fire Fighting Measure

Extinguishing media Recommended : Use caution when applying carbon dioxide in confined spaces. SMALL FIRE: Steam, CO₂, dry chemical or inert gas (e.g., nitrogen). LARGE FIRE: Use foam, water fog or water spray. Water fog and spray are effective in cooling containers and adjacent structures. However, water can cause frothing and/or may not extinguish the fire. Water can be used to cool the external walls of vessels to prevent excessive pressure, ignition or explosion. Not to be used : water jet

Hazards from the substance or mixture Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products Decomposition products may include the following materials : carbon dioxide, carbon monoxide

Special equipment for fire fighter Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6 Accidental release measurement

Personal precautions, protective equipment and emergency procedures No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations. Avoid all direct contact with the spilled material. Exclude sources of ignition and be aware of explosion hazard. Ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.

Environmental precautions Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities

Methods for cleaning up Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilled product.

SECTION 7 Handling and storage

- Handling** Vapor are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should be used only in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. No sparking tools should be used. Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see section 8. Always keep in containers made from the same material as the original one.
- Storage** Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from : Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

SECTION 8 Exposure control/personal protection

Ingredient	Exposure limit
Xylene	OSHA 2013 TWA : 100 ppm 435 mg/m ³
Ethylenediamine	OSHA PEL TWA : 10 ppm 25 mg/m ³
MIBK	OSHA REL TWA 50 ppm 205 mg/m ³
MEK	OSHA REL TWA 200 ppm 590 mg/m ³
IBA	OSHA PEL TWA 100 ppm 300 mg/m ³

Personal Protection


Use a NIOSH APPROVED RESPIRATOR
 Use GOGGLES OR FACE SHIELD
 RUBBER GLOVES AS NEEDED
 USE APRON OR OTHER CLOTHING TO AVOID SKIN CONTACT

Personil protective equipment should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Use a properly fitted, air-purifying or air fed respirator complying with an approved standard. Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.

- Engineering controls** Keep gas, vapor, or dust cocentration below any lower explosive limit. Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location

- Hygiene measures** Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.

SAFETY DATA SHEET

Date of issue : September 2021

SIMACOVER EP UNICOAT 2401-00 HARDENER
Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filter or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels

SECTION 9 Physical and chemical properties

Physical	Light Reddish Brown Liquid clear
Odor	Solvent-like
Flash point	Closed cup ; 35° C
Vapor density	Heavier than air
Specific density	0.95 ± 0.05 kg /litre
Viscosity	15-25 Second/DIN4
Solubilities	Insoluble in water

SECTION 10 Stability and reactivity

Reactivity and chemical stability	<p>Conditions to avoid : Avoid temperatures above 60°C (140 F), direct sunlight and contact with sources of heat.</p> <p>Hazardous reactions : Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.</p>
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced
Conditions to avoid	Avoid all possible sources of ignition (spark or flame). Do not pressurized, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition

SECTION 11 Toxicological information

Ingredient	Oral LD 50, mg/kg	Skin LD 50, mg/kg	Inhalation vapor LD 50, mg/l/4 hours
Ethylenediamine	1200 mg/kg, rat	730 mg/kg, rabbit	300 mg/m ³ , mouse
Xylene	4300 mg/kg, rat	>2000 mg/kg, rabbit	6350 ppm, rat
Isobutanol	2460 mg/kg rat	No data	No data
Methyl Ethyl Ketone	2737 mg/kg rat	No data	No data

SECTION 12 Ecological information

Ingredient	Species	Result
Ethylenediamine	Fish- Fathead Minnow; 96 hours	LC 50 = 115.7 mg/L
Xylene	Fish – Oncorhynchus mykiss; 96 hours	LC 50 = 8.2 mg/l

Environmental precaution : harmful to aquatic organism, may cause long term adverse effect in the aquatic environment.

SECTION 13 Disposal consideration

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations.

Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Spillage, remains, discarded clothes and similar should be discarded in a fireproof container.

The information presented below only applies to the material as supplied. The identification based on characteristic or listing may not apply if the material has been used or otherwise contaminated.

SAFETY DATA SHEET

Date of issue : September 2021

SIMACOVER EP UNICOAT 2401-00 HARDENER
SECTION 14 Transport information

Transport within user's premises	Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage
----------------------------------	---

	UN no.	Proper shipping name	class	Transport hazard class(es)	PG*	Env*	Additional information
ADR/RID Class	UN 1263	Paint	3 -		III	Yes	
IMDG Class	UN1263	Paint	3 -		III	Yes	
IATA Class	UN1263	Paint	3 -		III	Yes	

PG* : Packing group

Env* : Environmental hazards

SECTION 15 Regulatory information

Safety, health and environmental regulation/legislation specific for the substance or mixture

SECTION 16 Other information

Abbreviation and acronyms

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

Disclaimer

TO THE BEST OUR KNOWLEDGE, THE INFORMATION CONTAINED HERE IN IS ACCURATE. HOWEVER, NEITHER PT. SIGMA UTAMA NOR ANY SUBSIDIARIES ASSUMES ANY LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIAL MAY PRESENT UNKNOWN HAZARD AND SHOULD BE USED IN CAUTION. ALTHOUGH CERTAIN HAZARD ARE DESCRIBED HEREIN, WE CAN NOT GUARANTEE THAT THESE ARE THE ONLY HAZARD, WHICH EXIST.